



MICROLED – UNRIVALLED VISUAL EXPERIENCES.

COMMON CATHODE TECHNOLOGY

Resolution & colour superiority.

Experience the highest level of visual clarity with VIVID microLED. Chip on board (COB) delivers the most accurate representation of your photos and videos, bringing your content to life with a stunning DCI-P3 wide colour gamut.

With true 16-bit color, VIVID microLED can reproduce over 16.8 million colors with unmatched precision.

Our state-of-the-art calibration and pixel structure ensure that you always get the best colour quality possible. Upgrade to VIVID microLED and see the world in all its vivid, true-to-life glory.



* Easel TV stand sold separately



16 bit 
colour depth

Up to
40% 
peak brightness for
HDR photos and movies

16.8M 
on screen colours

Up to
30% 
energy saving

DCI-P3 
wide colour gamut

1,000,000:1 
high contrast ratio

HDR 



-  Industry-leading LED Technology
-  Ultra slim profile
-  Superior thermal performance
-  Superwide viewing angle
-  Razor-sharp motion
-  Up to 30 energy saving
-  Market leading image quality

Two sizes of cabinet



SPECIFICATIONS

VIVID microLED (21.6" cabinet)

PHYSICAL PARAMETERS				
Pixel Pitch (mm)	0.75	1.0	1.25	1.5
Unit Size (W × H × D)	480 × 270 × 28 mm 18.89 × 10.62 × 1.1 in	480 × 270 × 28 mm 18.89 × 10.62 × 1.1 in	480 × 270 × 28 mm 18.89 × 10.62 × 1.1 in	480 × 270 × 28 mm 18.89 × 10.62 × 1.1 in
Unit Weight (kg / lbs)	3.1 / 6.83	3.1 / 6.83	3.1 / 6.83	3.1 / 6.83
OPTICAL PARAMETERS				
Resolution	640 × 360	480 × 270	384 × 216	320 × 180
Aspect Ratio	16:9	16:9	16:9	16:9
Brightness (nits = cd/m²)	≤1000	≤1000	≤1000	≤1000
Contrast Ratio	≥1,000,000:1	≥1,000,000:1	≥1,000,000:1	≥1,000,000:1
Refresh Rate (Hz)	≤3840	≤3840	≤3840	≤3840
Frame Frequency (Hz)	60 / 3D: 120	60 / 3D: 120	60 / 3D: 120	60 / 3D: 120
Viewing Angle	178° / 178°	178° / 178°	178° / 178°	178° / 178°
Color Temperature (K)	3200 ~ 10000	3200 ~ 10000	3200 ~ 10000	3200 ~ 10000
Display Native Colour Space	DCI-P3	DCI-P3	DCI-P3	DCI-P3
ELECTRICAL PARAMETERS				
Power Consumption Max (W/m² / W/ft²)	≤500/46	≤450/42	≤450/42	≤450/42
Power Consumption Typical (W/m² / W/ft²)	≤170/16	≤150/14	≤150/14	≤150/14
Working Voltage	AC: 100V ~ 240V, 50 ~ 60Hz	AC: 100V ~ 240V, 50 ~ 60Hz	AC: 100V ~ 240V, 50 ~ 60Hz	AC: 100V ~ 240V, 50 ~ 60Hz
ADDITIONAL FEATURES				
System	Android OS 9.0	Android OS 9.0	Android OS 9.0	Android OS 9.0
Lifetime (Hours)	100,000	100,000	100,000	100,000
Operating Temp (°C / °F)	-20 ~ +60 / -4 ~ 42	-20 ~ +60 / -4 ~ 42	-20 ~ +60 / -4 ~ 42	-20 ~ +60 / -4 ~ 42
Humidity Range (%)	10 ~ 90	10 ~ 90	10 ~ 90	10 ~ 90

VIVID microLED (27" cabinet)

PHYSICAL PARAMETERS				
Pixel Pitch (mm)	0.78125	0.9375	1.25	1.5625
Unit Size (W × H × D)	600 × 337.5 × 28 mm 23.62 × 13.28 × 1.1 in	600 × 337.5 × 28 mm 23.62 × 13.28 × 1.1 in	600 × 337.5 × 28 mm 23.62 × 13.28 × 1.1 in	600 × 337.5 × 28 mm 23.62 × 13.28 × 1.1 in
Unit Weight (kg / lbs)	5.2 / 11.46	5.2 / 11.46	5.2 / 11.46	5.2 / 11.46
OPTICAL PARAMETERS				
Resolution	768 × 432	640 × 360	480 × 270	384 × 216
Aspect Ratio	16:9	16:9	16:9	16:9
Brightness (nits = cd/m²)	≤1000	≤1000	≤1000	≤1000
Contrast Ratio	≥1,000,000:1	≥1,000,000:1	≥1,000,000:1	≥1,000,000:1
Refresh Rate (Hz)	≤3840	≤3840	≤3840	≤3840
Frame Frequency (Hz)	60 / 3D: 120	60 / 3D: 120	60 / 3D: 120	60 / 3D: 120
Viewing Angle	178° / 178°	178° / 178°	178° / 178°	178° / 178°
Color Temperature (K)	3200 ~ 10000	3200 ~ 10000	3200 ~ 10000	3200 ~ 10000
Display Native Colour Space	DCI-P3	DCI-P3	DCI-P3	DCI-P3
ELECTRICAL PARAMETERS				
Power Consumption Max (W/m² / W/ft²)	≤600/56	≤500/46	≤450/42	≤450/42
Power Consumption Typical (W/m² / W/ft²)	≤200/19	≤170/16	≤150/14	≤150/14
Working Voltage	AC: 100V ~ 240V, 50 ~ 60Hz	AC: 100V ~ 240V, 50 ~ 60Hz	AC: 100V ~ 240V, 50 ~ 60Hz	AC: 100V ~ 240V, 50 ~ 60Hz
ADDITIONAL FEATURES				
System	Android OS 9.0	Android OS 9.0	Android OS 9.0	Android OS 9.0
Lifetime (Hours)	100,000	100,000	100,000	100,000
Operating Temp (°C / °F)	-20 ~ +60 / -4 ~ 42	-20 ~ +60 / -4 ~ 42	-20 ~ +60 / -4 ~ 42	-20 ~ +60 / -4 ~ 42
Humidity Range (%)	10 ~ 90	10 ~ 90	10 ~ 90	10 ~ 90



Please contact us if you have any questions,
we're always happy to help

www.theledstudio.com
sales@theledstudio.co.uk

UK Showroom

The Pavilion
Merchant Square
London, W2 1JZ
United Kingdom

Tel: +44 (0) 20 3832 9500

Head Office

Unit 3 Clearwater Business Park
Frankland Road
Swindon, SN5 8YZ
United Kingdom

Tel: +44 (0) 20 3832 9500

EMEA Office

169-171 Makarios III Avenue
Cedars Oasis Tower
3027, Limassol
Cyprus

Tel: +357 9626 8848

USA Office

22 Boston Wharf Rd
7th Floor
Boston, MA 02210
USA

Tel: +1 (508) 657-4622